

MPC KIT

MULTI-PURPOSE COMBO KIT

SCHONSTEDT 
INSTRUMENT COMPANY

Making Locating Easier Since 1953

**NEW FOR
2012**

REPLACES MAC-51BX



The most
portable,
versatile, and
accurate way to
Find it All
Underground

Magnetic Locator



Pipe & Cable Locator



CABLE TV LINES • CAST OR DUCTILE IRON PIPES

COPPER PIPE • CORNER MARKERS • CURB & VALVE BOXES

ENCLOSURES • FIBER OPTIC W/ TRACER OR SHIELD

GAS LINES • WEAPONS • HAZMAT DRUMS • IRRIGATION LINES

MAG & PK NAILS • MANHOLE COVERS • MARKER MAGNETS

MUNITIONS • PLASTIC PIPE W/ TRACER WIRE • POWER LINES

SEPTIC TANKS • STEEL PIPES • STREET LIGHT POWER

TELEPHONE LINES • WATER & SEWER LINES • WELL CASINGS

MPCKIT includes

- **GA-92XTd Magnetic Locator**
- **XTpc Pipe & Cable Locator**
- Inductive Antenna • Transmitter • Holster Clip • Ground Stake
- Power Supply & Charger for XTpc (AC/DC)
- Conductive Clips Assembly • Small Heavy Duty Conductive Clip
- Locating 101 Manual • Instruction Manual for XTpc & GA-92XTd
- Rugged carrying hard case with custom foam insert

Available in 3 models:

MPC-800: Includes an XTpc-82 Pipe & Cable Locator and a GA-92XTd Magnetic Locator

MPC-300: Includes an XTpc-33 Pipe & Cable Locator and a GA-92XTd Magnetic Locator

MPC-500: Includes an XT-512 Camera & Sonde Locator and a GA-92XTd Magnetic Locator



GA-92XTd Specifications

Output	Audio: Signal increases in frequency with gradient field intensity. Idle frequency = 10 Hz. Visual: Expanding bar-graphs indicate polarity (positive or negative) and relative signal strength
Battery Indicator	4-segment LCD
Gain	Continuous control
Volume	Continuous control
Input Power	Supplied by one 9 V battery (Lithium recommended, but not required)
Battery Life	24 Hours (intermittent usage)
Operating Temperature	-13° F to 140° F (25° C to 60° C)
Water Resistant Length	11.5 in (~29 cm) (when extended)
Overall Length	Unit extended: 26 in (~66 cm) Unit collapsed: 15.5 in (~39 cm)
Weight	Approximately 2.4 Lbs (1.1 Kg)

XTpc Receiver Specifications

Operating Frequency	82kHz or 33kHz plus 50/60Hz passive detection (factory selectable)
Battery	9 V single battery
Battery Life	18 hrs intermittent use
LCD Display	3 1/2 digit reflective Signal Strength, Directional Arrows, Battery Status, Volume and Depth
Controls	ON/Volume adjustment, OFF, DEPTH, SONDE, AUTO GAIN, UP gain, DOWN gain, PASSIVE
Dimensions	Unit extended: 26 in (~66 cm) Unit collapsed: 15.5 in (~39 cm)
Weight	Under 2.5 Lbs

XTpc Transmitter Specifications

Operating Frequency	82kHz or 33kHz (factory selectable)
Dimensions	7.2" L x 2.2" W x 1.5" H
Battery Type	Rechargeable NiMH 7.2 V, 3800mAh
Battery Life	8 hours continuous use
Output Power	Maximum 1-watt allowed under FCC at 82kHz; 1.8-watt at 33kHz
Controls	ON/OFF UP Power DOWN Power
LCD	3 1/2 digit reflective Battery Status, Mode, Output Power Level, Output Current (mA)
Weight	Under 2 lbs

Order/Info Hotline:
800-999-8280



Order/Info Online:
www.schonstedt.com



SCHONSTEDT 
INSTRUMENT COMPANY

Making Locating Easier Since 1953
an employee-owned company

MAGNETIC LOCATORS

Simply The Best



GA-52Cx

GA-72Cd

- Unmatched sensitivity
- Rapid response
- Locates quickly and easily
- Always on target

SCHONSTEDT 
INSTRUMENT COMPANY
Making Locating Easier Since 1953

SCHONSTEDT

GA-52Cx and GA-72Cd

Underground Locators...

Easy-To-Use

The **GA-52Cx** and **GA-72Cd** Locators find iron and steel objects underground. Both provide audio detection signals that peak in frequency when the locator's tip is held directly over the target. The GA-72Cd includes an easy-to-read digital and bar graph display showing signal strength and polarity.

**SCHONSTEDT
MADE IN USA**



GA-52Cx



GA-72Cd



Specifications	GA-52Cx	GA-72Cd
Audio Output	Tone frequency varies with gradient field intensity	Tone frequency varies with gradient field intensity(*)
Visual Indicator	N/A	Digital readout and bargraph indicate polarity and relative strength of magnetic field
Analog Output	N/A	Yes
Sensitivity	5 settings	4 settings
Input Power	2- Alkaline 9V batteries	2- Lithium 9V batteries
Battery Life	40 hrs (intermittent usage)	60 hrs (intermittent usage)
Battery Indicator	N/A	4-segment LCD
Weight	~ 2.5 Lbs (1.13 kg)	~ 2.6 Lbs (1.18 kg)
Operating Temperature	-13 to 140 F (-25 to 60 C)	-13 to 140 F (-25 to 60 C)
Overall Length	42.3 in (107.4 cm)	34.5 in (87.6 cm)
Waterproof Length	34.5 in (87.6 cm)	21 in (53.3 cm)
Sensor Spacing	20 in (50.8 cm)	14 in (35.6 cm)
Housing Material	Aluminum	Polycarbonate/ABS Blend

(*) This is the factory default audio output. An internal switch allows the user to change it to a fixed frequency and the volume varying with the gradient field intensity

Order/Info Hotline:
800-999-8280

Order/Info Online:
www.schonstedt.com

SCHONSTEDT 
INSTRUMENT COMPANY

Making Locating Easier Since 1953
an employee-owned company

FIND IT ALL UNDERGROUND

Pipe & Cable LOCATORS



TX5 Transmitter

TraceMaster II™



Transmitter

XTpc



Sondes

XT512



FaultMaster™

MAGNETIC LOCATORS



GA-52Cx



GA-92XT



GA-72Cd

**CONTACT YOUR LOCAL
SCHONSTEDT DEALER**

SCHONSTEDT 
INSTRUMENT COMPANY
Making Locating Easier Since 1953

www.schonstedt.com

55TH ANNIVERSARY

AN EMPLOYEE-OWNED COMPANY

MADE IN USA